

# Fork Type Stacker PF·A / PJ·A series

- ▲ Low profile forks can lift pallet easily.
- ▲ Ladder as option.
- ▲ **Non-marking castor as standard.**
- ▲ **Conforms to EN 1757-1:2001.**



**Noise-free Castor as option.**

**Option platform  
Model: LP10, LP20**



**PJ4150A  
Adjustable fork**



**PF4150A  
Fixed Fork**

i-Lift No. / Model (Fixed Fork)		1510301 / PF2085A	1510302 / PF2120A	1510303 / PF4085A	1510304 / PF4120A	1510305 / PF4150A
i-Lift No. / Model (Adjustable Fork)		1510306 / PJ2085A	1510307 / PJ2120A	1510308 / PJ4085A	1510309 / PJ4120A	1510310 / PJ4150A
Capacity	(kg)	200			400	
Max. Fork Height	(mm)	850	1200	850	1200	1500
Min. Fork Height	(mm)	85			85	
Fork Length	(mm)	600			650	
Fixed Fork Width (PF series)	(mm)	500			550	
Adjustable Fork Width (PJ series)	(mm)	215-500			235-500	
Load Roller	(mm)	Φ75			Φ75	
Steering Wheel	(mm)	Φ125			Φ125	
Pump Strokes to Max. Height		19	26	35	50	63
Overall Height	(mm)	1080	1435	1060	1410	1710
Overall Width	(mm)	560			590	
Overall Length	(mm)	1000	960	1040		
Net Weight	PF series (kg)	55	62	70	76	82
	PJ series (kg)	58	65	75	81	85
Option Platform		LP10F (For Fixed Fork) / LP10J (For Adjustable Fork)			LP20F (For Fixed Fork) / LP20J (For Adjustable Fork)	